



RED LINE PROFESSIONAL-SERIES 5W30TD MOTOR OIL



- Full-synthetic low-SAPS formula for passenger vehicles,
- OEM-certified for use under vehicle warranty
- For extended drain intervals and fuel economy of the latest global gasoline/petrol and direct-injection diesel engines with particulate filters

APPROVED / CERTIFIED:

- API SN**
ACEA C3-12
- BMW**
LL-04
- PORSCHE C30**
- MERCEDES BENZ**
MB-Approval 229.51*
- VW/AUDI**
507.00*
504.00*
- *Approval Pending**

RECOMMENDED FOR:

- MERCEDES BENZ**
MB 229.31
- CHRYSLER**
MS 11106
- GM**
dexos2®

dexos is a registered trademark of General Motors Corp.

TYPICAL PROPERTIES:

ACEA Service Class	C3-12
API Service Class	SN
SAE Viscosity Grade (Motor Oil)	5W-30
Vis @ 100°C, cSt	11.6
Vis @ 40°C, cSt	66
CCS Viscosity, Poise, @ °C	5900
Pour Point, °C	-49
Pour Point, °F	-56
NOACK Evaporation Loss, 1hr @ 482°F (250°C), %	9
HTHS Vis, cP @150°C, ASTM D4741	3.6

PACKAGE SIZES:

- 12104 – 5W30TD Prof Series – quart
12108 – 5W30TD Prof Series – 55 gallon

ABOUT RED LINE PROFESSIONAL-SERIES MOTOR OIL

- FULL SYNTHETIC -- OEM-required Group III/Group IV PAO Base Stocks
- Low volatility for reduced oil consumption
- Longlife certification for reduced wear protection following factory drain intervals
- For high- and low- mileage engines
- Compatible with conventional and synthetic oils
- Withstands extreme temperatures

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM